



(11)

EP 1 138 989 A2

(12)

EUROPEAN PATENT APPLICATION

(43) Date of publication:
04.10.2001 Bulletin 2001/40

(51) Int Cl.⁷: **F16K 7/12, F16K 31/122**

(21) Application number: 01104405.4

(22) Date of filing: 26.02.2001

(84) Designated Contracting States:
AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU
MC NL PT SE TR
 Designated Extension States:
AL LT LV MK RO SI

(30) Priority: 31.03.2000 JP 2000096332
10.05.2000 JP 2000137064

(71) Applicant: **Toyo Stainless Steel Industries Co., Ltd.**
Tsuyama-shi, Okayama (JP)


(72) Inventors:

- Iritani, Masao
1170-9, Kusakabe, Tsuyama-shi, Okayama (JP)
- Ozawa, Kaoru
1170-9, Kusakabe, Tsuyama-shi, Okayama (JP)
- Tateishi, Toru
1170-9, Kusakabe, Tsuyama-shi, Okayama (JP)

(74) Representative: **HOFFMANN - EITL**
Patent- und Rechtsanwälte
Arabellastrasse 4
81925 München (DE)

(54) **Diaphragm valve**

(57) A diaphragm valve can properly mount a peripheral portion of a diaphragm over the entire periphery and certainly establish a seal between the peripheral edge portion on a surface side of the diaphragm and a diaphragm mounting seat for preventing leakage of a liquid. The diaphragm valve includes an annular base (27) provided to project from a seat surface of said mounting seat (12) for a predetermined height and connected with a bracket mounting flange (16) on the side of said valve operating portion by bolts (17) and a diaphragm retaining portion (30) formed integrally with said flange (16) for compressing the peripheral edge portion of said diaphragm with a constant pressure so that said flange (16) and said base (27) are connected by said bolts (17) in the condition where said diaphragm (14) is compressed onto said base (12) with said constant pressure by said diaphragm retaining portion (30).



Description

BACKGROUND OF THE INVENTION

Field of the Invention

[0001] The present invention relates to a diaphragm valve to be used for opening and closing a flow path of a fluid piping, such as various liquid piping in food industry, pharmaceutical industry and so forth.

Description of the Related Art

[0002] Fig. 8 shows the conventional diaphragm valve. The diaphragm valve is constructed by fixing a peripheral edge portion on a surface side of a diaphragm 4 arranged in opposition to a valve seat 3 which is arranged within a valve body 1, on an annular diaphragm mounting seat 2 provided on a side wall portion 1a of the valve body, for opening and closing a flow path by moving the surface side of the diaphragm 4 toward and away from the valve seat 3 by driving in forward and reverse direction an actuation shaft of a valve operating portion 5 connected to a central position on a back surface side of the diaphragm 4. The valve operating portion 5 is formed with an air cylinder. A piston rod of the air cylinder serves as the actuation shaft. The air cylinder is mounted on the valve body 1 via a bracket 8.

[0003] As shown in Fig. 8, in the conventional diaphragm valve, the peripheral edge portion of the diaphragm 4 is fixed to the diaphragm mounting seat 2 by clamping the peripheral edge portion of the diaphragm between the diaphragm mounting seat 2 and a bracket mounting flange 6 of the valve operating portion 5 and by tightening four bolts 7 through the flange 6, the peripheral portion of the diaphragm 4 and the mounting seat 2. If tightening force of the bolts 7 is small, a force depressing the peripheral portion of the diaphragm onto the mounting seat lacks to cause leakage of a liquid. If the tightening force of the bolts 7 is too large, a force for depressing the peripheral edge of the diaphragm locally becomes large in the portion around the bolts 7 to form gaps between the diaphragm 4 and the mounting seat 2 between adjacent bolts 7 to cause leakage of the liquid. Therefore, adjustment of tightening force is difficult. Furthermore, there is personal error in tightening operation to cause significant difficulty in property fixing the peripheral portion of the diaphragm 4 onto the diaphragm mounting seat 2.

[0004] On the other hand, as shown in Fig. 9, the diaphragm 4 is consisted of a surface side membrane 4a of about 1 mm thick made of fluorine contained resin having superior chemical resistance, high water resistance and surface slip characteristics, such as Teflon (polytetrafluoroethylene: Registered Trademark of Du Pont), and a back surface side membrane 4b stacked on the backside surface, made of rubber and backing up the surface side membrane 4a. The rubber back sur-

face side membrane 4b causes little thermal expansion and thermal shrinking in response to temperature variation. On the other hand, the surface side membrane 4a of fluorine contained resin, such as Teflon has a property to expand up to a certain temperature and to cause shrinking at higher temperature. Therefore, sufficient shrinking margin W is provided for a peripheral edge portion of the surface side membrane 4a to be mounted on the mounting seat 2 of the valve body 1.

[0005] That is, as shown in Fig. 10, on the surface side peripheral edge portion of the surface side membrane 4a, an annular ridge 9 is formed along the peripheral edge portion for enhancing sealing effect with the diaphragm mounting seat 2 and the valve seat 3. Also, a linear ridge 10 extending in diametrical direction of the annular ridge 9 for the valve seat, is provided. A gap between the annular ridge 9 for establishing a seal between the diaphragm 4 and the diaphragm mounting seat 2 and an inner end edge of the diaphragm mounting seat 2 is the shrinking margin W. Thus, as can be appreciated from Fig. 7, if the shrinking margin W is wide, a gap S formed between the surface, liquid contacting surface of the surface side membrane 4a and the seat surface of the diaphragm mounting seat 2 becomes deep to increase tendency of penetration and trapping of the liquid therein to cause difficulty of washing. When the liquid is a food, such as milk, it becomes quite insanitary. It should be noted that, in Fig. 8, 4c is a bolt insertion holes provided at four corners of the diaphragm 4.

SUMMARY OF THE INVENTION

[0006] The present invention has been worked out in view of the problems set forth above. It is an object of the present invention to provide a diaphragm valve which can property mount a peripheral portion of a diaphragm over the entire periphery and certainly establish a seal between the peripheral portion on a surface side of the diaphragm and a diaphragm mounting seat for preventing leakage of a liquid.

[0007] Another object of the present invention to provide a diaphragm valve which can minimize a shrinking margin provided on a surface side membrane of the diaphragm, and whereby can make a gap formed between a liquid contacting surface of the surface side membrane and a seat surface of the diaphragm mounting seat to facilitate washing of the gap.

[0008] According to the first aspect of the present invention, a diaphragm valve fixing a peripheral edge portion on a surface side of a diaphragm arranged in opposition to a valve seat

within a valve body, on an annular diaphragm mounting seat provided in a predetermined portion of the valve body and driving an actuation shaft of a valve operating portion connected to a central portion on back surface side of the diaphragm back and forth in an axial direction to abutting and releasing the surface side of diaphragm

with respect to the valve seat for opening and closing a flow passage, comprising:

an annular base provided to project from a seat surface of the mounting seat for a predetermined height and connected with a bracket mounting flange on the side of the valve operating portion by bolts; and

a diaphragm retaining portion formed integrally with the flange for compressing the peripheral edge portion of the diaphragm with a constant pressure so that the flange and the base are connected by the bolts in the condition where the diaphragm is compressed onto the base with the constant pressure by the diaphragm retaining portion.

[0009] According to the second aspect of the present invention, a diaphragm valve fixing a peripheral edge portion on a surface side of a diaphragm arranged in opposition to a valve seat within a valve body, on an annular diaphragm mounting seat provided in a predetermined portion of the valve body and driving an actuation shaft of a valve operating portion connected to a central portion on back surface side of the diaphragm back and forth in an axial direction to abutting and releasing the surface side of diaphragm with respect to the valve seat for opening and closing a flow passage, comprising:

the diaphragm being consisted of a surface side membrane of fluorine contained resin and a back surface side membrane of rubber laminated on back surface of the surface side membrane; the surface side membrane 14a having an annular ridge portion extending along a peripheral edge portion and an annular projection extending circumferentially at the inner side of the annular ridge portion; and

the diaphragm mounting seat having an annular projection on inside of the peripheral edge thereof and an annular groove extending along outer periphery of the annular projection for engaging with the annular ridge portion for abutting the annular projection onto the annular projection of the diaphragm mounting seat.

[0010] According to a third aspect of the present invention, a diaphragm valve fixing a peripheral edge portion on a surface side of a diaphragm arranged in opposition to a valve seat within a valve body, on an annular diaphragm mounting seat provided in a predetermined portion of the valve body and driving an actuation shaft of a valve operating portion connected to a central portion on back surface side of the diaphragm back and forth in an axial direction to abutting and releasing the surface side of diaphragm with respect to the valve seat for opening and closing a flow passage, comprising:

the diaphragm being consisted of a surface side

membrane of fluorine contained resin and a back surface side membrane of rubber laminated on back surface of the surface side membrane; the surface side membrane 14a having an annular ridge portion extending along a peripheral edge portion and an annular projection extending circumferentially at the inner side of the annular ridge portion; and

the diaphragm mounting seat having an annular projection on inside of the peripheral edge thereof; an annular base provided to project from a seat surface of the mounting seat for a predetermined height and connected with a bracket mounting flange on the side of the valve operating portion by bolts;

an annular groove extending along outer periphery of the annular projection for engaging with the annular ridge portion for abutting the annular projection onto the annular projection of the diaphragm mounting seat; and

a diaphragm retaining portion formed integrally with the flange for compressing the peripheral edge portion of the back surface side membrane and the surface side membrane of the diaphragm with a constant pressure so that the flange and the base are connected by the bolts in the condition where the diaphragm is compressed onto the base with the constant pressure by the diaphragm retaining portion.

[0011] In the preferred construction, a retaining surface of the diaphragm retaining portion is located at a position projecting from an abutting surface of the bracket mounting flange abutting onto the annular base for a predetermined length. The diaphragm may be showed into circular shape. The valve operating portion may be formed with a cylinder connected to a bracket mounted on the side of the valve body, a piston rod of the cylinder forms the actuation shaft.

[0012] It is also preferred that the valve operating portion (45) comprises a threaded shaft (38) threadingly engaged with the bracket (18) mounted on the side of the valve body (11) and a handle (39) operated for driving the threaded shaft (38) for rotation, and the threaded shaft (38) serves as the actuation shaft.

[0013] According to the fourth aspect of the present invention, a diaphragm valve fixing a peripheral edge portion on a surface side of a diaphragm arranged in opposition to a valve seat within a valve body and driving an actuation shaft of a valve operating portion connected to a central portion on back surface side of the diaphragm back and forth in an axial direction to abutting and releasing the surface side of diaphragm with respect to the valve seat for opening and closing a flow passage, comprising:

a sensor body including a sealed casing formed with an infiltration membrane in a part, which permits a liquid to pass from outside to inside of the sealed casing

and does not permit the liquid to pass from inside to outside of the sealed casing, a strong electrolyte filled in the sealed casing, a pair of electrodes arranged within the sealed casing in opposition with each other, the sensor body being provided at a position where the infiltration membrane contacts with the liquid leaking to a back-side of the diaphragm, and a detection circuit for detecting a conductive state between the electrodes within the sealed casing.

[0014] Preferably, the diaphragm may be consisted of a surface side membrane of fluorine contained resin and a back surface side membrane of rubber laminated on back surface of the surface side membrane, and a leakage announcing conduit is provided in the back surface side membrane.

[0015] Other objects will become more clear from the discussion given hereinafter.

BRIEF DESCRIPTION OF THE DRAWINGS

[0016] The present invention will be understood more fully from the detailed description given hereinafter with reference to the accompanying drawings of the preferred embodiment of the present invention, which, however, should not be taken to be limitative to the present invention, but are for explanation and understanding only.

[0017] In the drawings:

Fig. 1 is a longitudinally half sectioned front elevation of the preferred embodiment of a diaphragm valve according to the present invention;

Fig. 2 is a bottom view of the diaphragm valve of Fig. 1;

Fig. 3A is a front elevation of the diaphragm;

Fig. 3B is a section taken along line X - X of Fig. 3A;

Fig. 4 is an enlarged partial section of the diaphragm valve shown in Fig. 1;

Fig. 5 is a longitudinally half sectioned front elevation of a diaphragm valve having a manually operable valve operating portion;

Fig. 6 is a half sectioned front elevation of another embodiment of a diaphragm valve with a leakage detection sensor according to the present invention;

Fig. 7 is an enlarged partial section of the diaphragm valve shown in Fig. 6;

Fig. 8 is an enlarged partially sectioned front elevation of the conventional diaphragm valve;

Fig. 9 is an enlarged partial view of the conventional diaphragm valve shown in Fig. 8; and

Fig. 10 is a front elevation of the conventional diaphragm valve.

DESCRIPTION OF THE PREFERRED EMBODIMENT

[0018] Fig. 1 is a longitudinally half sectioned front elevation of the preferred embodiment of the diaphragm valve according to the present invention, and Fig. 2 is a

bottom view thereof. In Figs. 1 and 2, the reference numerals 11 denotes a cylindrical valve body. At a central portion in the longitudinal direction of the valve body 11, an inwardly projecting dam portion 23 serving as a valve seat 13 is provided. The reference numeral 12 denotes a diaphragm mounting seat for mounting a peripheral edge portion on a surface side of a diaphragm 14. The diaphragm mounting seat 12 is formed on a side wall portion 11a of the valve body 11. On the inside of the diaphragm mounting seat 12, valve openings 21a and 22a communicated with inlet and outlet pipe portions 21 and 22 formed on opposite sides across the dam portion 23.

[0019] The diaphragm 14 is consisted of a surface side membrane 14a formed of fluorine contained resin and a back surface side membrane 14b formed of rubber stacked on a back surface side of the surface side membrane 14a. Both membranes 14a and 14b are connected by a connecting shaft 24 mounted in the central portion thereof. As shown in Fig. 3, the surface side membrane 14a is formed into a disc shaped configuration of about 1 mm thick of Teflon as fluorine contained resin. On the peripheral edge portion of the surface, an annular ridge portion of quadrangular cross section is projected. Adjacent the inner periphery of the annular ridge portion 25, an annular projection 19 is projected. Also, a linear projection 20 diametrically connecting the annular projection 19 is projected. The back surface side membrane 14b is formed of a synthetic resin strong against temperature variation, into a disc shaped configuration with about 4 mm thick and a slightly greater diameter than that of the surface side membrane 14a. On the back surface of the back surface side membrane 14b, a metallic retainer 26 is arranged. The retainer 26, the back surface side membrane 14b and the surface side membrane 14a are integrally connected via the connecting shaft 24 so as not to cause relative angular displacement with respect to each other.

[0020] As shown in Figs. 1 and 4, on the outer periphery side of the diaphragm mounting seat 12, an annular base 27 connected with a bracket mounting flange 16 on the side of a operating portion 15 by means bolts is projected at a predetermined height. On the other hand, adjacent the inner periphery of the annular base 27, an annular projection 28 is projected upwardly to define an annular groove 29 adjacent the outer periphery thereof in cooperation with the annular base 27. In this case, a seat surface of the diaphragm mounting surface 12 is substantially the upper surface of the annular projection 28.

[0021] On the other hand, on the bracket mounting flange 16, an annular diaphragm retaining portion 30 is projected from the inner peripheral portion thereof. A retaining surface 30a at the lower end of the diaphragm retaining portion 30 is projected downwardly from an abutting surface 16a of the bracket mounting flange 16 for a length α , as shown in Fig. 4. By forming an annular body by projecting the diaphragm retaining portion 30

from the abutting surface 16a of the flange 16, the peripheral portion of the diaphragm 14 can be effectively compressed. The projecting length α of the diaphragm retaining portion 30 is set in a length to compress the peripheral portion of the diaphragm 14 to firmly fitting the annular projection 19 onto the annular projection 28 with a constant pressure in the condition where the peripheral portion of the diaphragm 14 having a predetermined thickness is engaged with the diaphragm mounting seat 12 as shown. In setting the projecting length α of the diaphragm retaining portion 30, a projecting height of the annular projection 28 from the diaphragm mounting seat 12, a thickness of the diaphragm 14 and a elastic module of the diaphragm 14 are taken into account.

[0022] An engaging groove 32 is formed in the diaphragm retaining portion 30 for receiving an anti-rotation pin 31 projected from a retainer 26. the anti-rotation pin 31 serves not only for preventing the diaphragm 14 from rotating but also as positioning means for properly positioning the linear projection 20 projecting from the surface of the surface side membrane 14a on the valve seat 13. On the other hand, in the bracket mounting flange 16 and the annular base 27 on the side of the valve body 11, bolt holes 16a and 27a are formed at four portions, respectively. The diaphragm retaining portion 30 may be provided in a form detachable from the bracket mounting flange 16.

[0023] As shown in Fig. 1, the valve operating portion 15 is formed with an air cylinder connected to a bracket 18 formed with the flange 16 at the lower end. The cylinder 15 is constructed with a cylinder body 33, a piston 34 and a piston rod 35 reciprocating in axial direction integrally with the piston 34. The piston rod 35 serves as the actuation shaft of the diaphragm valve. The lower end piston rod (actuation shaft) 35 is connected to the retainer 26 so that the diaphragm 14 is forms to vary mode between a valve closing mode where the diaphragm 14 is in contact with the valve seat 13 as shown by the solid line of Fig. 1 and a valve opening mode where the diaphragm 14 is placed away from the valve seat 13 as shown by phantom line in Fig. 1 by reciprocal motion of the piston rod 35 in the axial direction. As shown in Fig. 1, a part of the bracket 18 forms a lower end wall portion 33a of the cylinder body 33. In Fig. 1, the reference numeral 36 denotes a coil spring normally biasing the piston toward valve closing side.

[0024] Next, discussion will be given for a method for mounting and securing the diaphragm 14 onto the diaphragm mounting seat 12 of the valve body 11. At first, in the condition where the bracket 18 is removed from the valve body 11, the diaphragm 14 is fitted onto the diaphragm mounting seat 12 surrounded the outer periphery by the annular base 27 to engage the annular ridge portion 25 into the groove 29 formed along the outer side of the annular projection 28 on the side of the mounting seat 12, to abut the annular projection 19 onto the annular projection 28 of the mounting seat 12, and

to abut the linear projection 20 onto the valve seat 13. From this condition, with mounting the flange 16 of the bracket 18 on the annular base 27, the lower end portion of the diaphragm retaining portion 30 is pushed into an annular groove 37 formed on the back surface side of the back surface side membrane 14b. Then, bolt 17 is threaded into the threaded hole 16a of the flange 16 from the threaded hole 27a of the annular base 27 to connect the flange 16 with the annular base 27 by bolts.

[0025] Thus, by fastening the flange 16 onto the annular base 27 by four bolts 17, the diaphragm retaining portion 30 compresses the peripheral portion of the diaphragm 14 over the entire periphery to depress the annular projection 19 of the surface side membrane 14a onto the annular projection 28 of the diaphragm mounting seat 12, and whereby to establish complete seal between the surface side membrane 14a and the annular projection 28 of the mounting seat 12. At this time, a pressure applied to the peripheral portion of the diaphragm 14 by the diaphragm retaining portion 30 is constant as set by the projecting height of the annular projection 19 from the diaphragm mounting seat 12, the thickness of the diaphragm 14 and the elastic modules of the diaphragm 14. Therefore, what is required is to tighten the bolts 17 to fasten the flange 16 onto the annular base 27. Accordingly, over-tightening or lack of tightening of the bolts 17 will never be caused. Also, irrespective of the person who tighten the bolt, no personal error in the tightening operation will be caused to certainly fix the peripheral edge portion of the diaphragm portion 14 over the entire periphery of the diaphragm seat 12 to assure prevention of liquid leakage.

[0026] On the other hand, with the mounting structure of the diaphragm 14 set forth above, the surface side membrane 14a of the diaphragm has the annular ridge portion 25 projected along the peripheral edge portion and the annular projection 19 extending circumferentially at inner side of the annular ridge portion 25. The annular ridge portion 25 on the surface side membrane 14a is engaged with the annular groove 29 formed on the outer circumference of the annular projection 28 to abut the annular projection 19 of the surface side membrane 14a onto the annular projection 28 of the diaphragm mounting seat 12. Therefore, even if the surface side membrane 14a formed of fluorine contained resin, such as Teflon or the like, causes shrinking by the high temperature liquid flowing through the flow path, the annular ridge portion 24 of the surface side membrane 14a restricts the annular groove 29 formed on the outer circumference of the mounting seat 28 to restrict shrinking of the surface side membrane 14a. Accordingly, as shown in Fig. 4, the annular projection 19 of the surface membrane 14a can be arranged in the vicinity of the inner peripheral edge of the diaphragm mounting seat 12 as close as possible. Thus, a shrinking margin w as a gap between the annular projection 19 of the surface side membrane 14a and the mounting seat 12 can be set as narrow as possible.

[0027] Since the shrinking margin w is quite narrow as possible, a gap may not be formed between the surface of the surface side membrane 14a and the diaphragm mounting seat. Even when the gap is formed, the gap is shallow to easily accumulate a liquid to facilitate cleaning and is quite sanitary. On the other hand, since the peripheral edge portion of the diaphragm 14 is not bolted by providing the bolt holes as in the prior art in order to mounting and fixing the diaphragm 14 on the diaphragm mounting seat 12, the diaphragm 14 can be formed into circular shape and whereby to permit saving of the material.

[0028] Fig. 5 shows a diaphragm valve having a manually operable valve operating portion 45. In the construction of the valve operating portion 45, like components to those of the diaphragm valve shown in Figs. 1 to 4 will be identified by like reference numerals and redundant discussion for such common component will be omitted in order to keep the disclosure simple enough to facilitate clear understanding of the present invention. The valve operating portion 45 is constructed with a cylindrical threaded portion 18a at the upper end portion of the bracket 18 mounted on the side of the valve body 11, a threaded shaft 38 to meshing engagement with the cylindrical threaded portion 18a and a handle to be operated manually for rotating the threaded shaft 38. The threaded shaft 38 serves as the actuation shaft. Accordingly, by rotating the threaded shaft by manually gripping the handle, the threaded shaft is shifted back and forth in axial direction to vary the mode of the diaphragm between the valve closing mode abutting onto the valve seat 13 and the valve opening mode released away from the valve seat 13.

[0029] With the preferred embodiment of the diaphragm valve according to the present invention set forth above, by tightening the bolts to fasten the bracket mounting flange onto the annular base of the valve body, the diaphragm retaining portion uniformly compresses the entire circumference of the peripheral edge portion of the diaphragm to press the peripheral edge portion onto the diaphragm mounting seat. Thus, a complete seal can be established between the peripheral edge portion on the surface side of the diaphragm and the diaphragm mounting seat. At this time, the pressure to be exerted on the peripheral edge portion of the diaphragm through the diaphragm retaining portion can be a constant pressure preliminarily set in consideration of the projecting height of the annular projection from the diaphragm mounting seat, the thickness of the diaphragm and the elastic modules of the diaphragm. Therefore, it is only required to fasten the flange onto the annular base by tightening the bolts so as not to cause over tightening or lack of tightening, and not to cause personal error in tightening operation. Thus, the peripheral edge portion of the diaphragm can be properly fixed on the diaphragm mounting seat over the entire circumference to certainly prevent liquid leakage.

[0030] On the other hand, with the diaphragm valve

according to the present invention, since the diaphragm is provided with the annular ridge portion extending along the peripheral edge portion and the annular projection extending circumferentially at the inner side of the annular ridge portion, and the diaphragm mounting seat is provided with the annular projection. In the annular groove defined on the outer circumference of the annular projection, the annular projection of the diaphragm is engaged to abut the annular ridge portion of the diaphragm onto the annular projection of the diaphragm mounting seat. Therefore, even if the surface side membrane 14a formed of fluorine contained resin, such as Teflon or the like, causes shrinking by the high temperature liquid flowing through the flow path, the annular ridge portion of the surface side membrane restricts the annular groove formed on the outer circumference of the mounting seat to restrict shrinking of the surface side membrane. Accordingly, the annular projection of the surface membrane can be arranged in the vicinity of the inner peripheral edge of the diaphragm mounting seat as close as possible. Thus, a shrinking margin as a gap between the annular projection of the surface side membrane 14a and the mounting seat can be set as narrow as possible. Since the shrinking margin is quite narrow as possible, a gap may not be formed between the surface of the surface side membrane 14a and the diaphragm mounting seat. Even when the gap is formed, the gap is shallow to easily accumulate a liquid to facilitate cleaning and is quite sanitary.

[0031] On the other hand, as shown in the embodiment of the present invention, the retaining surface of the diaphragm retaining portion can effectively compress the peripheral edge portion of the diaphragm since the diaphragm retaining portion is placed at the position projected for a predetermined length from the abutting surface of the bracket mounting flange abutting onto the annular base.

[0032] Furthermore, as shown in the embodiment of the present invention, since the diaphragm can be formed into circular shape material to form the diaphragm can be reduced to achieve material saving.

[0033] Furthermore, as shown in the embodiment of the present invention, when the valve operating portion is formed with the cylinder connected with the bracket mounted on the side of the valve body, driving of the actuation shaft back and forth in axial direction can be done automatically. Also, when the valve operating portion is formed with the threaded shaft threadingly engaged with the bracket mounted on the side of the valve body side, and the handle rotatingly operating the threaded shaft, back and forth driving of the actuation shaft in the axial direction can be simply and easily operated manually.

[0034] Figs. 6 and 7 show another embodiment of the diaphragm valve according to the present invention, in which a liquid leakage detection sensor is provided in the diaphragm valve. Namely, in the conventional diaphragm valve, the diaphragm forming the valve body is

mounted at a position opposing to the valve seat in the valve body in a manner isolating the surface side contacting with the liquid and the back surface side. By back and forth driving of the actuation shaft connected to the central portion on the back surface side in axial direction, the surface side of the diaphragm moved toward and away from the valve seat to open and close the flow passage. Thus, in such diaphragm valve, the diaphragm may seal the surface side and the back surface side having the actuation mechanism with the fastening portion of the peripheral edge portion to constantly contact the liquid only with the surface side. Also, valve operation can be performed only by deformation of the diaphragm so as not to require any sliding contact portion, such as a valve shaft portion of various other valves, which easily cause leakage of the liquid. Thus, for high sealing ability in the valve portion, it is particularly useful for the field of food industry, pharmaceutical industry and so forth which requires high reliability in safety and sanitary.

[0035] In the meanwhile, when breakage is caused in the diaphragm of the diaphragm valve employed in a manufacturing line of the liquid, namely, in a pure water line or the like, it becomes necessary to have a function for detecting the breakage in order to avoid continuous production of defective liquid. Conventionally, it has been employed a method to regularly exchange the diaphragm at earlier timing before occurrence of breakage of the diaphragm, to be not economical to dispose the diaphragm of the condition usefully for sufficiently long period by early exchange.

[0036] On the other hand, as the conventional leakage detection sensor provided in the diaphragm valve, it have been known a sensor, in which a conductive rubber layer is provided in the diaphragm for electrically detecting liquid leakage. In case of the pure water line in the pharmaceutical industry, or the like, because of quite low conductivity of the pure water, liquid leakage cannot be detected accurately and thus is poorly practical.

[0037] The embodiment shown in Figs. 6 and 7, in view of the problem set forth above, even in the case of the liquid having quite low conductivity, such as the pure water, it becomes possible to provide the liquid leakage detection sensor of the diaphragm which can be certain detect liquid leakage.

[0038] Discussion will be given for the diaphragm with the liquid leakage sensor with reference to Figs. 6 and 7. In the following discussion, like components to those of the former embodiment diaphragm valve will be identified by like reference numerals and redundant discussion for such common component will be omitted in order to keep the disclosure simple enough to facilitate clear understanding of the present invention. It should be noted that, in the following discussion, the construction unique in the shown embodiment will be discussed primarily. As shown in Figs. 6 and 7, the liquid leakage sensor assembly includes a sensor body 50 inserted within an opening portion 60 provided at a predetermined position in the bracket 18, and a detection circuit

51 formed by leading outside of the bracket 18 from the sensor body 50. Also, in the back surface side membrane 4b serving as the back-up membrane of the diaphragm, a leakage announcing conduit 10 is formed.

5 [0039] As shown in Fig. 7, the sensor body 50 is constructed with a sealed casing 54 formed with a box-shaped casing body 52 opening in one side surface, an infiltration membrane 53 arranged in the opening surface side of the casing body 52, a strong electrolyte filled in the sealed casing 54, and a pair of electrodes a and b respectively serving as anode and cathode arranged in opposition. The infiltration membrane 53 is a membrane arranged in the opening surface side of the casing body 52 so as to permit penetration of liquid from outside of the sealed casing 54 into the inside but block leakage of the liquid within the casing 54 to the outside.

10 [0040] The strong electrolyte to be filled within the sealed casing 54 of the sensor body 50 may be NaCl (sodium chloride to be used as a salt or the like) in the preferred embodiment. However, other material, such as NaOH (caustic soda, sodium hydroxide and the like) may also be used. As shown in Fig. 4, the detection circuit 51 is an electric circuit including the electrodes a and b arranged within the sealed casing 54, a power source 55 which is formed with a battery, an ammeter 56 and a lamp 57.

15 [0041] Upon mounting of the sensor body 50 onto the opening portion 60 of the bracket 18, the casing body 52 is mounted and fixed via a sealing member 58 in the condition where the infiltration membrane 53 is located at a position contacting with the liquid leaking to the back surface side of the diaphragm 14.

20 [0042] In the liquid leakage detection sensor constructed as set forth above, assuming that the shown diaphragm valve is disposed within the pure water line, if the surface side membrane 14a causes breakage, the water (pure water) leaking to the back surface side through the broken portion of the surface of the surface side membrane 14a penetrates into a gap between the back surface of the surface side membrane 14a and the surface of the back surface side membrane 14b. Then, the leaking liquid flows into the inside of the bracket 18, namely, into the space portion S on the back surface side of the leakage announcing conduit 59 of the back surface side membrane 14b to be accumulated therein, through the leakage announcing conduit 59. The leaked water accumulated in the space portion S passes through the infiltration membrane 53 arranged in the sealed casing 54 of the sensor body 50 and then is mixed with NaCl within the sealed casing 54. Once the leaking water is admixed with NaCl, NaCl is dissociated into Na ion (+) and Cl ion (-), namely electrolytically dissociated, for high dielectric constant of the water. Furthermore, since NaCl is strong electrolyte, it is completely dissociated in the water (no molecule which is not dissociated will be remained).

25 [0043] When electrolytic dissociation of NaCl is caused in the leaked water penetrated into the sealed

casing 54 of the sensor body 50, as set forth above, dielectric constant of the water is increased to establish conductive state between the electrodes a and b. Conductive state between the electrodes a and b can be detected by turning ON of the lamp 57. Also, a degree of conduction can be seen from an indication of the ammeter 56. Accordingly, occurrence of breakage of the surface side membrane 14a of the diaphragm 14 can be detected by the liquid leakage detection sensor.

[0044] With the diaphragm valve with the liquid leakage detection sensor, even in case of the liquid having quite low conductivity, such as pure water, leakage from the surface side membrane 14a can be certainly detected. On the other hand, the diaphragm 14 is consisted of the thin surface side membrane 14a of fluorine contained resin and the thick back-up membrane 14b of rubber stacked on the back surface side. By providing the liquid leakage announcing conduit 59 in the back-up membrane 14b, the water leaking through the broken portion of the surface side membrane 14a immediately flows out to the back surface side of the diaphragm 14 through the liquid leakage announcing conduit 59 to contact with the sensor body 50. Therefore, breakage of the surface side membrane 14a can be detected quickly.

[0045] While discussion has been given for detection of leakage of pure water in the pure water line, the liquid leakage sensor can detect not only the pure water but also leakage of liquids other than pure water.

[0046] With the diaphragm valve of the shown embodiment, upon breakage of the diaphragm, the liquid leaking out the backside surface is admixed with the strong electrolyte within the casing through the infiltration membrane of the sensor body to cause electrolytic dissociation of the strong electrolyte to increase electric conductivity of the liquid to detect conductive state of between the electrodes within the casing to detect breakage of the diaphragm. Accordingly, the diaphragm can be used for extended period throughout its life. Particularly, with the liquid leakage sensor, even in case of the liquid having low conductivity, such as pure water, leakage of the liquid due to breakage of the surface side membrane can be certainly detected.

[0047] Furthermore, with the shown embodiment, since the diaphragm is formed with the thin surface side membrane of fluorine contained resin and the thick back-up membrane of rubber stacked on the back surface side, and by providing the liquid leakage announcing conduit in the back-up membrane, breakage of the surface side membrane can be detected quickly.

[0048] Although the present invention has been illustrated and described with respect to exemplary embodiments thereof, it should be understood by those skilled in the art that the foregoing and various changes, emission and additions may be made therein and thereto, without departing from the spirit and scope of the present invention. Therefore, the present invention should not be understood as limited to the specific em-

bodiment set out above but to include all possible embodiments which can be embodied within a scope encompassed and equivalent thereof with respect to the feature set out in the appended claims.

Claims

1. A diaphragm valve fixing a peripheral edge portion on a surface side of a diaphragm (14) arranged in opposition to a valve seat (13) within a valve body (11), on an annular diaphragm mounting seat (12) provided in a predetermined portion of said valve body (11) and driving an actuation shaft (34, 45) of a valve operating portion (15) connected to a central portion on back surface side of said diaphragm back and forth in an axial direction to abutting and releasing the surface side of diaphragm (14) with respect to said valve seat (13) for opening and closing a flow passage, comprising:

an annular base (27) provided to project from a seat surface of said mounting seat (12) for a predetermined height and connected with a bracket mounting flange (16) on the side of said valve operating portion by bolts (17); and a diaphragm retaining portion (30) formed integrally with said flange (16) for compressing the peripheral edge portion of said diaphragm with a constant pressure so that said flange (16) and said base (27) are connected by said bolts (17) in the condition where said diaphragm (14) is compressed onto said base (12) with said constant pressure by said diaphragm retaining portion (30).

2. A diaphragm valve fixing a peripheral edge portion on a surface side of a diaphragm (14) arranged in opposition to a valve seat (13) within a valve body (11), on an annular diaphragm mounting seat (12) provided in a predetermined portion of said valve body (11) and driving an actuation shaft (34, 45) of a valve operating portion (15) connected to a central portion on back surface side of said diaphragm back and forth in an axial direction to abutting and releasing the surface side of diaphragm (14) with respect to said valve seat (13) for opening and closing a flow passage, comprising:

said diaphragm (14) being consisted of a surface side membrane (14a) of fluorine contained resin and a back surface side membrane (14b) of rubber laminated on back surface of said surface side membrane (14a);
said surface side membrane 14a having an annular ridge portion (25) extending along a peripheral edge portion and an annular projection (19) extending circumferentially at the inner

- side of said annular ridge portion (25); and said diaphragm mounting seat (12) having an annular projection (28) on inside of the peripheral edge thereof and an annular groove (29) extending along outer periphery of said annular projection (28) for engaging with said annular ridge portion (25) for abutting said annular projection (19) onto said annular projection (28) of said diaphragm mounting seat (12).
3. A diaphragm valve fixing a peripheral edge portion on a surface side of a diaphragm (14) arranged in opposition to a valve seat (13) within a valve body (11), on an annular diaphragm mounting seat (12) provided in a predetermined portion of said valve body (11) and driving an actuation shaft (34, 45) of a valve operating portion (15) connected to a central portion on back surface side of said diaphragm back and forth in an axial direction to abutting and releasing the surface side of diaphragm (14) with respect to said valve seat (13) for opening and closing a flow passage, comprising:
- said diaphragm (14) being consisted of a surface side membrane (14a) of fluorine contained resin and a back surface side membrane (14b) of rubber laminated on back surface of said surface side membrane (14a);
- said surface side membrane 14a having an annular ridge portion (25) extending along a peripheral edge portion and an annular projection (19) extending circumferentially at the inner side of said annular ridge portion (25); and
- said diaphragm mounting seat (12) having an annular projection (28) on inside of the peripheral edge thereof;
- an annular base (27) provided to project from a seat surface of said mounting seat (12) for a predetermined height and connected with a bracket mounting flange (16) on the side of said valve operating portion by bolts (17);
- an annular groove (29) extending along outer periphery of said annular projection (28) for engaging with said annular ridge portion (25) for abutting said annular projection (19) onto said annular projection (28) of said diaphragm mounting seat (12); and
- a diaphragm retaining portion (30) formed integrally with said flange (16) for compressing the peripheral edge portion of said back surface side membrane (14b) and said surface side membrane (14a) of said diaphragm with a constant pressure so that said flange (16) and said base (27) are connected by said bolts (17) in the condition where said diaphragm (14) is compressed onto said base (12) with said constant pressure by said diaphragm retaining portion (30).

4. A diaphragm valve as set forth in claim 1, wherein a retaining surface (30a) of said diaphragm retaining portion (30) is located at a position projecting from an abutting surface of said bracket mounting flange (16) abutting onto said annular base (27) for a predetermined length.
5. A diaphragm valve as set forth in claim 1, wherein said diaphragm (14) is showed into circular shape.
6. A diaphragm valve as set forth in claim 1, wherein said valve operating portion (15) is formed with a cylinder connected to a bracket (18) mounted on the side of said valve body (11), a piston rod (35) of said cylinder forms said actuation shaft.
7. A diaphragm valve as set forth in claim 1, wherein said valve operating portion (45) comprises a threaded shaft (38) threadingly engaged with said bracket (18) mounted on the side of said valve body (11) and a handle (39) operated for driving said threaded shaft (38) for rotation, and said threaded shaft (38) serves as said actuation shaft.
8. A diaphragm valve fixing a peripheral edge portion on a surface side of a diaphragm (14) arranged in opposition to a valve seat (13) within a valve body (11) and driving an actuation shaft (35) of a valve operating portion 15 connected to a central portion on back surface side of said diaphragm back and forth in an axial direction to abutting and releasing the surface side of diaphragm (14) with respect to said valve seat (13) for opening and closing a flow passage, comprising:
- a sensor body (50) including a sealed casing (54) formed with an infiltration membrane (53) in a part, which permits a liquid to pass from outside to inside of said sealed casing and does not permit the liquid to pass from inside to outside of said sealed casing (54), a strong electrolyte filled in said sealed casing, a pair of electrodes (a, b) arranged within said sealed casing in opposition with each other, said sensor body being provided at a position where said infiltration membrane (53) contacts with the liquid leaking to a backside of said diaphragm (14), and a detection circuit (2) for detecting a conductive state between said electrodes (a, b) within said sealed casing (54).
9. A diaphragm valve as set forth in claim 1, wherein said valve fixing a peripheral edge portion on a surface side of a diaphragm (14) arranged in opposition to a valve seat (13) within a valve body (11) and driving an actuation shaft (35) of a valve operating portion 15 connected to a central portion on back surface side of said diaphragm back and forth in an axial direction to abutting and releasing the surface side of diaphragm (14) with respect to said valve

seat (13) for opening and closing a flow passage, comprising:

a sensor body (50) including a sealed casing (54) formed with an infiltration membrane (53) in a part, which permits a liquid to pass from outside to inside of said sealed casing and does not permit the liquid to pass from inside to outside of said sealed casing (54), a strong electrolyte filled in said sealed casing, a pair of electrodes (a, b) arranged within said sealed casing in opposition with each other, said sensor body being provided at a position where said infiltration membrane (53) contacts with the liquid leaking to a backside of said diaphragm (14), and a detection circuit (2) for detecting a conductive state between said electrodes (a, b) within said sealed casing (54).

10. A diaphragm valve as set forth in claim 8 or 9, wherein said diaphragm is consisted of a surface side membrane (14a) of fluorine contained resin and a back surface side membrane (14b) of rubber laminated on back surface of said surface side membrane (14a), and a leakage announcing conduit (59) is provided in said back surface side membrane (14b).

30

35


40



45

50

55

FIG.1








FIG.5





FIG.6






FIG.8




FIG.9





FIG.10



(19)



Europäisches Patentamt
European Patent Office
Office européen des brevets



(11)

EP 1 138 989 A3

(12)

EUROPEAN PATENT APPLICATION

(88) Date of publication A3:
14.05.2003 Bulletin 2003/20

(51) Int Cl.7: **F16K 7/12, F16K 31/122,**
G01M 3/18, G01M 3/04

(43) Date of publication A2:
04.10.2001 Bulletin 2001/40

(21) Application number: **01104405.4**

(22) Date of filing: **26.02.2001**

(84) Designated Contracting States:
AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU
MC NL PT SE TR
Designated Extension States:
AL LT LV MK RO SI

(30) Priority: **31.03.2000 JP 2000096332**
10.05.2000 JP 2000137064


(71) Applicant: **Toyo Stainless Steel Industries Co.,**
Ltd.
Tsuyama-shi, Okayama (JP)

(72) Inventors:
• **Iritani, Masao**
1170-9, Kusakabe, Tsuyama-shi, Okayama (JP)
• **Ozawa, Kaoru**
1170-9, Kusakabe, Tsuyama-shi, Okayama (JP)
• **Tateishi, Toru**
1170-9, Kusakabe, Tsuyama-shi, Okayama (JP)

(74) Representative: **HOFFMANN - EITLE**
Patent- und Rechtsanwälte
Arabellastrasse 4
81925 München (DE)

(54) Diaphragm valve

(57) A diaphragm valve can properly mount a peripheral portion of a diaphragm over the entire periphery and certainly establish a seal between the peripheral edge portion on a surface side of the diaphragm and a diaphragm mounting seat for preventing leakage of a liquid. The diaphragm valve includes an annular base (27) provided to project from a seat surface of said mounting seat (12) for a predetermined height and connected with a bracket mounting flange (16) on the side of said valve operating portion by bolts (17) and a diaphragm retaining portion (30) formed integrally with said flange (16) for compressing the peripheral edge portion of said diaphragm with a constant pressure so that said flange (16) and said base (27) are connected by said bolts (17) in the condition where said diaphragm (14) is compressed onto said base (12) with said constant pressure by said diaphragm retaining portion (30).



EP 1 138 989 A3



European Patent
Office

EUROPEAN SEARCH REPORT

Application Number
EP 01 10 4405

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.7)
X	FR 2 373 734 A (KLEIN SCHANZLIN & BECKER AG) 7 July 1978 (1978-07-07)	1,4-7	F16K7/12
A	* page 1, line 40 - page 3, line 10; figure *	9	F16K31/122
	---		G01M3/18
			G01M3/04
X	DE 31 23 028 A (WALDENMAIER J E H) 5 January 1983 (1983-01-05)	1,5,7	
A	* page 14, line 16 - line 27 *	2,3	
	* page 16, line 4 - page 17, line 13; figures 1-4 *		

Y	US 4 901 751 A (STORY CARL E ET AL) 20 February 1990 (1990-02-20)	8,10	
A	* column 3, line 57 - column 4, line 32; figures *	1,9	

Y	FR 2 740 873 A (BOULET D AURIA STANISLAS) 9 May 1997 (1997-05-09)	8,10	
A	* page 3, line 1 - page 4, line 30; figure 1 *	1,9	

A	FR 2 287 633 A (MUGUET FERNAND) 7 May 1976 (1976-05-07)	1,4,5,7	TECHNICAL FIELDS SEARCHED (Int.Cl.7)
	* page 6, line 14 - line 22; figure *		F16K
	---		G01M
A	US 2 988 322 A (HARRY ANDERSON JOHN) 13 June 1961 (1961-06-13)	1,4,5,7	
	* figure 1 *		

A	PATENT ABSTRACTS OF JAPAN vol. 1998, no. 11, 30 September 1998 (1998-09-30) & JP 10 169802 A (SMC CORP), 26 June 1998 (1998-06-26)	1-6	
	* abstract; figure *		

	-/--		
The present search report has been drawn up for all claims			
Place of search THE HAGUE		Date of completion of the search 20 March 2003	Examiner Lanel, F-B
<p>CATEGORY OF CITED DOCUMENTS</p> <p>X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document</p> <p>T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document</p>			

EPO FORM 1503 03/02 (P04001)



European Patent
Office

EUROPEAN SEARCH REPORT

Application Number
EP 01 10 4405

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.7)
A	EP 0 882 921 A (FURON CO) 9 December 1998 (1998-12-09) * column 6, line 56 - column 7, line 11; figures 2,5 * -----	1,8,9	
			TECHNICAL FIELDS SEARCHED (Int.Cl.7)
The present search report has been drawn up for all claims			
Place of search THE HAGUE		Date of completion of the search 20 March 2003	Examiner Lane1, F-B
CATEGORY OF CITED DOCUMENTS X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document			

EPO FORM 1503 (3.12.02) (P0401)



European Patent
Office

Application Number

EP 01 10 4405

CLAIMS INCURRING FEES

The present European patent application comprised at the time of filing more than ten claims.

- ☐ Only part of the claims have been paid within the prescribed time limit. The present European search report has been drawn up for the first ten claims and for those claims for which claims fees have been paid, namely claim(s):
- ☐ No claims fees have been paid within the prescribed time limit. The present European search report has been drawn up for the first ten claims.

LACK OF UNITY OF INVENTION

The Search Division considers that the present European patent application does not comply with the requirements of unity of invention and relates to several inventions or groups of inventions, namely:

see sheet 8

- ☒ All further search fees have been paid within the fixed time limit. The present European search report has been drawn up for all claims.
- ☐ As all searchable claims could be searched without effort justifying an additional fee, the Search Division did not invite payment of any additional fee.
- ☐ Only part of the further search fees have been paid within the fixed time limit. The present European search report has been drawn up for those parts of the European patent application which relate to the inventions in respect of which search fees have been paid, namely claims:
- ☐ None of the further search fees have been paid within the fixed time limit. The present European search report has been drawn up for those parts of the European patent application which relate to the invention first mentioned in the claims, namely claims:



European Patent
Office

LACK OF UNITY OF INVENTION
SHEET B

Application Number
EP 01 10 4405

The Search Division considers that the present European patent application does not comply with the requirements of unity of invention and relates to several inventions or groups of inventions, namely:

1. Claims: 1-7

Characteristics related to a diaphragm of a diaphragm valve.

2. Claims: 8,1+9,10

Diaphragm valve with a leakage sensor.

**ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.**

EP 01 10 4405

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report. The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

20-03-2003

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
FR 2373734	A	07-07-1978	BE 861572 A1	31-03-1978
			BR 7708117 A	25-07-1978
			CH 624456 A5	31-07-1981
			ES 464810 A1	01-09-1978
			FR 2373734 A1	07-07-1978
			IT 1087895 B	04-06-1985
			LU 78635 A1	20-04-1978
			NL 7712240 A	09-06-1978
			SE 7713537 A	07-05-1978
DE 3123028	A	05-01-1983	DE 3123028 A1	05-01-1983
US 4901751	A	20-02-1990	AT 137578 T	15-05-1996
			DE 69026824 D1	05-06-1996
			DE 69026824 T2	05-12-1996
			EP 0477304 A1	01-04-1992
			JP 2552957 B2	13-11-1996
			JP 5500414 T	28-01-1993
			KR 9601999 B1	09-02-1996
			WO 9015977 A1	27-12-1990
FR 2740873	A	09-05-1997	FR 2740873 A1	09-05-1997
FR 2287633	A	07-05-1976	FR 2287633 A1	07-05-1976
US 2988322	A	13-06-1961	NONE	
JP 10169802	A	26-06-1998	NONE	
EP 0882921	A	09-12-1998	US 6000416 A	14-12-1999
			EP 0882921 A2	09-12-1998
			JP 11051218 A	26-02-1999

EPO FORM P0459

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82

